

## 淄博聚硕锌业有限责任公司氧化锌技术指标

氧化锌 (99.7%) JSQB-02  
※Zinc Oxide(99.7%)  
优于国标«GB/T3185-92»

分子式: ZnO

分子量: 81.39

\*Molecular fomula: ZnO Molecular weight: 81.39

用途: 广泛用于橡胶、涂料、玻璃、陶瓷、日化、电子及食品和医药。

\*Purpose:It is used in rubber,coating,glass,  
cosmetics,colorant,Electron and food industries.

产品技术指标:

\*The technical values:

项 目 Item	指 标 Indices
氧化锌 (干基) % zinc oxide (counted on dry basis )	≧ 99.7
金属物 (以 Zn 计) % metal zinc	无 N.D
氧化铅 (以 Pb 计) % Lead oxide (counted on Pb)	≤ 0.003—0.0005
氧化镉 (以 Cd 计) % Cadmium oxide (counted on Cd )	≤ 0.0005
氧化锰 (以 Mn 计) % Manganes oxide (counted on Mn )	≤ 0.0001
氧化铜 (以 Cu 计) % Copper oxide (counted on Cu)	≤ 0.0002
盐酸不溶物 % Matter insoluble in HCL	≤ 0.006
干燥失重 % loss of weight in drying	≤ 0.3
灼烧减量 % Loss of weight on ignition	≤ 0.2
水溶物 % Matter soluble in water	≤ 0.1
筛余物 (μm) % Residue on 45μm sieve	≤ 0.1

此产品通过 SGS 检测。符合欧盟环保指令。